

UP TO
5 mm
PER COAT



MILAPRO F1

INTERIOR READY MIXED SURFACE FILLER



- ▶ **HIGH FILLING POWER ON CEMENT / CONCRETE**
- ▶ **UP TO 5 MM PER COAT**
- ▶ **WHITE**

Fabriqu  par TOUPRET

PURPOSE

Ready to use surface filler to level damaged and irregular substrates, interior use, manual application.

SUBSTRATES

MILAPRO F1 can be applied on:

- Cement plaster
- Painted or unpainted / new or renovated substrates
- Plasterboard
- Old textured surfaces
- Gypsum Plaster
- Concrete
- Old roughcast

OVERCOATING

By any type of surface fillers, wall coverings, mat or satin finish paints.

Physical and technical FEATURES

MILAPRO F1: Surface filler in paste form for interior use, made of mineral components and synthetic resins.

- Characterization (NFT 36-005): Family III-Class 2
- Codification (EN 16 566): $G_3S_3V_0W_0A_0C_0R_0$
- Application thickness: Up to 5 mm
- Consumption: 300 - 500 gr/m² for a fine surfacing according to thickness and substrate
- Second coat: once the first coat is dry
- Overcoat: When fully dry
- Colour: White

USE AND STORAGE CONDITIONS

- Application tool: Blade or trowel
- Tools cleaning : With water.
- Preservation: product guaranteed 6 months, from the original purchase invoice date as evidence, stored in a dry place, away from frost and sun.

PACKAGING

- Buckets of 25 kg

RECOMMENDATIONS AND CARE FOR USE

- Do not apply under a temperature < 8  C and > 35  C nor under an hygrometry rate over 70%.
- Do not apply on overheated surfaces
- Do not apply on damp substrates
- Do not apply on polystyrene, nor on wall paper, nor on exterior substrates.

SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS TO BE REFERRED TO

- NFT 16566: Coating fillers for interior works and/or exterior.
- NFT 36-005: Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.
- French DTU 59.4 (NFP 74-204): wall papers and wall coverings processing

HEALTH AND SAFETY

- No danger tag.
- Safety data sheets available on www.toupretpro.co.uk or toupret.com.

The data sheet information, especially the guidelines relevant to the application and final use of **MILAPRO F1** are provided in good faith and result from the knowledge of the products and experience of TOUPRET company. The product is required to be applied as per the trade practices rules book and in reference to our recommendations. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.